

8-Cup Drip Coffee Brewer

ONE-TOUCH WITH THERMAL CARAFE

MSRP: \$179.99 USD

For cafe quality coffee at the touch of a button, the 8-Cup Brewer offers curated features that mimic the artisan pour-over brewing method.

Endorsed by the Specialty Coffee Association to make the coveted Golden Cup, our brewers are trusted by cafes from coast to coast and used by judges in World Coffee Competitions.



bonavita

bonavita.co sales@bonavita.co

A good morning, every morning

- One-touch brew action with auto-off makes it oh-so simple to make a complex and full-bodied cup of coffee.
- Cafe-quality coffee without the wait. Make an 8-cup carafe in 6 minutes.
- Easy cleaning. The carafe lid, filter basket, and showerhead are all dishwasher safe and the plastic is BPA-free.

Designed by professionals

1500 WATT HEATER

Powerful and precise, the heater maintains optimal brewing temperature of 195° to 205°F (91° to 96°C).

PRE-INFUSION MODE

Mimics the artisan pour-over brewing method by giving the coffee grounds time to bloom.

🕨 LARGE SHOWERHEAD DESIGN

Facilitates even saturation of coffee grounds and uniform flavor extraction.

DOUBLE WALLED THERMAL CARAFE

Double walled stainless steel thermal carafe keeps coffee hot for hours.

What they're saying



"The Bonavita is one of the faster models we tested, and it earned high scores in nearly all of our tastings." - Serious Eats



"Possibly the last drip-coffee machine you'll ever want to own, Bonavita's 1900TS aims to revolutionize the at-home coffee experience." - Digital Trends





SKU: BV1900TS UPC: 645240811674

Specifications

| | Product | Product with Box |
|--|------------|--|
| Length | 12.4" | 12.8" |
| Width | 6.8" | 7.9" |
| Height | 12.2" | 13.9" |
| Weight | 5.8 lbs. | 8.2 lbs. |
| Capacity | 8 cups | |
| Cord Length | 2 ft (24") | |
| Stainless Steel k Double-walled s thermal carafe | Ť | BPA-free plastic water tank, carafe lid, filter basket, and showerhead |
| Plug Type | | Type B (for U.S. and Canada) |
| | | 120 Volts |
| Voltage Current | | |
| Current | | 12.5 Amps 195°-205°F (91°-96°C) |
| | | |

PRODUCT CERTIFICATIONS

SCA Certified, ETL certified

